



Esempio di ordinativo: Codice
Example of purchasing order: Code

Questa Guida a "L" tipo GLX e GLZ viene utilizzata a lato dei carrelli con movimento longitudinale. Risolve contemporaneamente l'esigenza di ritegno del carrello mobile sullo stampo e il suo scorrimento in parete. La Guida a "L" tipo GLX o GLZ non necessita di spinatura nella relativa sede. L'esecuzione precisa del profilo a "L" permette l'intercambiabilità nel tempo. Guida temprata a cuore (55 HRC) e rettificata.

La guida a "L" tipo GLX o GLZ può essere tagliata con una normale troncatrice per espulsori e, grazie alla foratura a passo, è possibile utilizzarne anche il più piccolo spezzone.

This Guide "L" type GLX and GLZ is used to side of the undercarriages with longitudinal movement. It resolves at the same time requirement of containment of the mobile undercarriage on the stamp and it's slide in wall. Guide "L" type GLX or GLZ doesn't need plug in the relative center. The precise execution of the profile "L" provides interchangeability in time. Guide is tempered in heart (55 HRC) and rectified.

Guide "L" type GLX or GLZ can be cut with a normal miter saws for ejectors and, thanks to step perforation, it's possible to use also smaller fragment of it.

Guida a "L" Guide to "L"	Codice - Code GLX	Codice - Code GLZ
A	14 ⁰ -0,020	14 ⁰ -0,020
B	14 ⁰ +0,020	9 ⁰ +0,020
C	24 ⁰ +0,040	19 ⁰ +0,040
D	19 ⁰ -0,040	19 ⁰ -0,040
E	14 ⁰ +0,020	14 ⁰ +0,020
F	2 ⁰ -0,020	2 ⁰ -0,020
Y Vite TCEI UNI 2383 Screw TCEI UNI 2383	M6	M6
Passo fori Hole footstep	25	25
Lungh. Tot. Total length	500 ±1	500 ±1

Esempi d'impiego
Employment examples

