

## R0479-12-0009

### Smerigliatrice angolare con pinza da 6 mm SMD90

Angular grinder with 6mm clamp SMD90



#### Descrizione:

Smerigliatrice angolare con pinza da 6mm.  
E' indicata per utilizzo con mole abrasive, frese in metallo duro e mandrini da tela abrasiva.

#### Description:

Angle grinder with 6mm clamp.  
Designed to be used with abrasive grindstones, hard metal fraises and mandrels for abrasive cloth.

#### Caratteristiche tecniche Technical specifications

|                       |                |                        |                 |
|-----------------------|----------------|------------------------|-----------------|
| Pinza Standard        | Ø 6 mm         | Standard Clamp         | Ø 6 mm          |
| N°giri                | 18000 giri/min | Rotation speed         | 18000 turns/min |
| P max. di esercizio   | 6 bar          | Max. working power     | 6 bar           |
| Attacco utensile max. | 7 mm           | Tool's attachment max. | 7 mm            |
| Dimensioni            | F 44 x 178 mm  | Dimensions             | F 44 x 178 mm   |
| Peso                  | 700 g          | Weight                 | 700 g           |

## R0479-12-0010

### Smerigliatrice dritta con pinza da 3 mm LFX030

Straight air grinder with 3 mm collet LFX030



#### Descrizione:

Smerigliatrice dritta con pinza da 3mm.  
E' Indicata per tutte quelle operazioni di smerigliatura che necessitano di un attrezzo leggero preciso e potente.

#### Description:

Straight grinder with 3mm clamp.  
Designated to be used in all grinding works that need use of light, accurate and powerful tool.

#### Caratteristiche tecniche Technical specifications

|                 |                |                    |                 |
|-----------------|----------------|--------------------|-----------------|
| Corsa           | 0,3 mm         | Collet             | 0,3 mm          |
| N°giri          | 65000 giri/min | RPM                | 65000 turns/min |
| Consumo area    | 90 l/min       | Air consumption    | 90 l/min        |
| Pressione cons. | Ø30 x 205 mm   | Operating pressure | Ø30 x 205 mm    |
| Dimensione      | F 28 x 220 mm  | Dimensions         | F 28 x 220 mm   |
| Peso            | 78 g           | Weight             | 78 g            |